Date Printed: 7/20/2006 Page: 1

Product Code: 02111SSC

Product Name: WASH PRIMER ACID COMPONENT, PART B

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: 800-424-9300

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(See top of page)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component/Exposure Limits	CAS#	% by Wt.
ISOPROPYL ALCOHOL ACGIH TLV/TWA - 400 PPM OSHA PEL - 500 PPM = STEL OTHER INFORMATION: 400 PPM	67-63-0	91.97
PHOSPHORIC ACID ACGIH TLV/TWA - 1.0 MG/M3 OSHA PEL - 1.0 MG/M3 STEL - 3 MG/M3	7664-38-2	4.38

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if inhaled. May cause the following effects: Nose, throat and respitory tract irritation. Allergic respitory reaction. May cause lung damage. Eye and skin irritation. Allergic skin reaction.

FLAMMABLE LIQUID

Keep away from heat, sparks, and flame.

Vapors may cause flash fire.

Toxic gases/fumes are given off during burning or thermal decomposition.

EYE CONTACT:

Irritating. Will injure eye tissue if not removed promptly.

SKIN CONTACT:

Contains corrosive material. May cause burns to the skin. Frequent or prolonged contact may irritate and cause dermatitis. Low order of toxicity.

PRIMARY ROUTES OF ENTRY:

Skin absorption.

Dermal and inhalation.

INGESTION:

Date Printed: 7/20/2006 Page: 2

Product Code: 02111SSC

Product Name: WASH PRIMER ACID COMPONENT, PART B

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: 800-424-9300

If swallowed, consult a physician immediately.

INHALATION:

High vapor concentrations are irritating to the eyes and respiratory tract. May cause headaches, dizziness, other central nervous system effects.

CHRONIC INFORMATION:

See Section 11.

CARCINOGENICITY:

See Section 11.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Asthma and other respiratory ailments; chemical sensitization.

4. FIRST AID MEASURES

EYE CONTACT:

Flush immediately with large amounts of running water for at least 15 minutes while lifting eyelids. Take to a physician for medical treatment.

SKIN CONTACT:

Remove product and immediately flush affected area with water for at least 15 minutes. Remove contaminated clothing and shoes. Launder before reuse. Except in the most minor, superficial and localized burns, cover affected area with sterile dressing or clean sheeting and transport for medical care. DO NOT APPLY GREASES OR OINTMENTS. Control shock, if present. Call a physician. Victims with a major skin area contact should remain under medical observation for at least 24 hours due to possible delayed effects.

INGESTION:

If swallowed, CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

Do not induce vomiting.

INHALATION:

Move patient to fresh air. If breathing has stopped or is labored, give assisted respiration (eg. mouth-to-mouth). Supplemental oxygen may be indicated. Prevent aspiration of vomit. Turn victim's head to the side. Assure mucous does

Date Printed: 7/20/2006 Page: 3

Product Code: 02111SSC

Product Name: WASH PRIMER ACID COMPONENT, PART B

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: 800-424-9300

not obstruct airway. Call a physician.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION PROPERTIES:

FLASH POINT (deg.F):

53

METHOD:

Tag Closed Cup

FLAMMABLE LIMITS % :

Lower limit: 2 Upper limit: 12

AUTOIGNITION TEMPERATURE:

N/A

EXTINGUISHING MEDIA:

Carbon Dioxide, Dry Chemical or Foam.

FIREFIGHTING PROCEDURES AND EQUIPTMENT:

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flames. Closed container may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near product container (even empty) because product (even residue) can ignite explosively. Full protective equipment including self-contained breathing apparatus should be worn.

Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up or possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

During a fire, irritating and highly toxic gases (See

Section 10, Incompatibilites data) and smoke are present from the decomposition/combustion products.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED :

Evacuate all non-essential personnel and remove all sources of ignition (flames, hot surfaces, electrical, static and frictional sparks). Ventilate area. Equip clean-up crew with appropriate protective equipment. Avoid breathing vapors. Avoid skin contact. Prevent entry into drains, sewers and waterways. Notify appropriate authorities if necessary. Contain and remove with inert absorbent and nonsparking tools.

Date Printed: 7/20/2006 Page: 4

Product Code: 02111SSC

Product Name: WASH PRIMER ACID COMPONENT, PART B

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: 800-424-9300

7. HANDLING AND STORAGE

HANDLING:

Use only with adequate ventilation. Avoid prolonged breathing of vapors. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates that vapor/mist levels are below applicable exposure limits. Follow respirator manufacturer's directions for use. Use grounding and bonding connection when transferring material to prevent static discharge, fire or explosion. Avoid free fall of liquid in excess of a few inches. Use sparkproof tools and explosion proof equipment.

STORAGE:

Do not store above 120 F or below 32 F. Store large quantities in buildings designed to comply with OSHA's 29 CFR 1910.106. Keep away from heat, sparks and open flame. Keep containers closed when not in use. Keep closures tight and upright to prevent leakage. Emptied containers may retain hazardous residue. Follow all hazard precautions in this data sheet until container is thoroughly cleaned or destroyed. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below current applicable OSHA safety and health requirements in the mixing, application and curing areas; and to remove decomposition products during welding and flame cutting on surfaces coated with this product.

RESPIRATORY PROTECTION:

When spray applied and when used in limited ventilation areas, wear a NIOSH/MSHA approved organic vapor/particulate respirator designed to remove a combination of particulate, gas and vapor. When used in confined areas or poorly ventilated areas, use a NIOSH/MSHA approved air line type respirator or hood. During sanding or grinding operations,

Date Printed: 7/20/2006 Page: 5

Product Code: 02111SSC

Product Name: WASH PRIMER ACID COMPONENT, PART B

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: 800-424-9300

use a NIOSH approved particulate respirator to remove solid airborne particles of sanding dust. Use NIOSH approved respirators when flame cutting, welding or hazing material coated with this product. Observe OSHA regulations for respirator use (29 CFR 1910.134). Air monitoring of the workplace may be required to determine appropriate respirator selection.

EYE PROTECTION:

Use safety eyewear with splash guards or side shields. A full face shield may be appropriate. Contact lenses should not be worn.

SKIN PROTECTION:

It is good industrial hygiene practice to minimize skin contact. Chemical resistant gloves are required for prolonged or repeated contact. An apron may be appropriate to protect against skin contact. Prevent prolonged skin contact with contaminated clothing. Wash contaminated clothing before reuse.

OTHER PROTECTIVE EQUIPMENT AND GUIDLINES:

Safety showers and eye wash stations should be available. Educate and train employees in the safe use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:

Liquid.

APPEARANCE:

Clear liquid.

ODOR:

Solvent odor.

VOC (LB/GL):

6.42 lb/gl

VOC (grams/liter):

769 g/l

WEIGHT PER GALLON:

6.767 lb/gl

SPECIFIC GRAVITY:

.8127

%EXEMPT SOLVENT by WEIGHT:

3.65

%EXEMPT SOLVENT by VOLUME:

3.

BOILING POINT (deg. F):

Date Printed: 7/20/2006 Page: 6

Product Code: 02111SSC

Product Name: WASH PRIMER ACID COMPONENT, PART B

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: 800-424-9300

177

WATER SOLUBILITY:

Negligible.

FREEZING POINT (deg. F):

N/A

10. STABILITY AND REACTIVITY

STABILITY:

Stable under normal conditions.

HAZARDOUS POLYMERZATION:

Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce hazardous fumes when heated to decomposition as in welding. Fumes may contain the following: Carbon Monoxide, Carbon Dixoide, Hydrogen Chloride Gas, and Chlorine fumes when heated to decomposition.

INCOMPATIBILITIES (MATERIALS TO AVOID):

Bases, metals, amines, alcohols, and oxidizing agents

11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

Has not been tested as a whole for acute effects.

CHRONIC EFFECTS:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage, liver and kidney damage. Long term overexposure effects are not currently known.

Has not been tested as a whole for chronic effects.

CARCINOGENICITY:

Has not been tested as a whole for carcinogenicity effects.

MUTAGENICITY:

Has not been tested as a whole for mutagenicity effects.

REPRODUCTIVE EFFECTS:

Has not been tested as a whole for reproductive effects.

Date Printed: 7/20/2006 Page: 7

Product Code: 02111SSC

Product Name: WASH PRIMER ACID COMPONENT, PART B

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: 800-424-9300

DEVELOPMENTAL EFFECTS:

Has not been tested as a whole for developmental effects.

12. ECOLOGICAL INFORMATION

ECOLOGICAL EFFECTS:

Has not been tested as a whole for ecological effects.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS:

Recycle, fuel blend or incinerate. Dispose of in accordance with applicable laws and regulations. It is the responsibility of the owner of the waste to dispose of it properly. Laboratory analysis is recommended to profile the waste for proper disposal determination.

U.S E.P.A WASTE NUMBER AND DESCRIPTION:

D001, D002 Waste Flammable Liquid, Corrosive N.O.S.

HAZARDOUS WASTE CHARACTERISTICS:

Corrosive.

14. TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME:

Flammable Liquid, Corrosive, N.O.S.

UN NUMBER:

UN2924

DOT HAZARD CLASS:

DOT LABEL:

Flammable Liquid, Corrosive.

DOT PACKAGING GROUP:

PG II

U.S POSTAL SERVICE:

Will not handle.

15. REGULATORY INFORMATION

Date Printed: 7/20/2006 Page: 8

Product Code: 02111SSC

Product Name: WASH PRIMER ACID COMPONENT, PART B

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: 800-424-9300

(Not meant to be all inclusive - selected regulations represented)

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372: CAS#7664-38-2 Phosphoric Acid

TSCA STATUS:

All ingredients are listed on the TSCA inventory.

STATE REGULATIONS:

This product may contain chemicals that fall under individual state Right-to-Know regulatory requirements. See Section 2 for material listings. For details on regulatory requirements, contact the appropriate agency in your state.

16. OTHER INFORMATION

Date of issue: 7/20/2006

Last Revision Date:

HMIS Information

HEALTH: 2

FLAMMABILITY: 4
REACTIVITY: 1

PERSONAL PROTECTIVE EQUIPMENT:

DISCLAIMER:

This MSDS is provided as an informational resource only. The information is received from a combination of sources, including raw material suppliers and is believed to be reliable and accurate. It does not intend to be all-inclusive and shall only be used as a guide. Changing reporting requirements and other uncontrolled variables make it impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to verify its information as well as determine the proper personal protection based on conditions of use. The buyer assumes all responsibility for the use and handling of this product in accordance with the Federal, State and Local laws and regulations. Hentzen Coatings, Inc. makes no representation or warranty regarding the accuracy of this information nor that the information or data will not change.