



# Material Safety Data Sheet

Issuing Date: 22-Dec-2011

Revision Date: 08-Oct-2013

Version: 7.1

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: 08609TUZ-B33

Product Name: TAN 686A, 33446 VOHAP FREE ZENTHANE,  
MIL-DTL-53039E, TYPE IX

Hentzen Coatings, Inc.  
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200  
Emergency Telephone: ChemTrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

Harmful by inhalation

Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates  
May cause central nervous system depression  
Flammable liquid and vapor

### Potential Health Effects

#### Principle Routes of Exposure

Inhalation, Skin Contact, Eye Contact

#### Acute Toxicity

##### Eyes

Prolonged contact may result in chemical burns to the eyes. Blindness may occur.

##### Skin

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Severe skin irritant. Repeated or prolonged contact: Causes severe irritation and or burns.

##### Inhalation

May cause allergic respiratory reaction. May be harmful if inhaled. May cause irritation of respiratory tract. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Exposure well above the exposure limits may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in the lungs). As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. These symptoms could be immediate or delayed up to several hours after exposure and could include chest tightness, wheezing, cough or asthmatic attack. Anesthetic. Isocyanates may cause acute irritation and/or sensitization of the respiratory system leading to tightness of the chest, wheeziness and an asthmatic condition. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Chronic overexposure to isocyanates has also been reported to cause lung damage, including decrease in lung function, which may be permanent.

##### Ingestion

Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration may cause pulmonary edema and pneumonitis.

#### Chronic Toxicity

No known effect based on information supplied.

#### Aggravated Medical Conditions

Central nervous system. Preexisting eye disorders. Skin disorders. Respiratory disorders. Peripheral Nervous System (PNS). Lungs.

#### Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

#### Environmental hazard

See Section 12 for additional Ecological Information.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Hazardous Components

Chemical Name	CAS-No	Weight	ACGIH TLV	OSHA PEL
METHYL AMYL KETONE	110-43-0	30% - 40%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m <sup>3</sup>
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE	28182-81-2	10% - 20%	-	-
TITANIUM DIOXIDE	13463-67-7	10% - 20%	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust
CHROMIC OXIDE	1308-38-9	0% - 5%	TWA: 0.5 mg/m <sup>3</sup> Cr	TWA: 0.5 mg/m <sup>3</sup> Cr (vacated) TWA: 0.5 mg/m <sup>3</sup> Cr
ORGANIC TIN COMPOUND	77-58-7	0% - 5%	STEL: 0.2 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> Sn S*	TWA: 0.1 mg/m <sup>3</sup> Sn (vacated) TWA: 0.1 mg/m <sup>3</sup> Sn (vacated) S*

#### 4. FIRST AID MEASURES

**General advice**

Immediate medical attention is required. Show this material safety data sheet to the doctor in attendance.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin Contact**

Wash off immediately with soap and plenty of water. Consult a physician is necessary. For severe exposure, remove clothing and use safety shower. Seek medical attention.

**Inhalation**

Consult a physician. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Asthmatic type symptoms can be immediate or deferred up to several hours.

**Ingestion**

Do NOT induce vomiting.

#### 5. FIRE-FIGHTING MEASURES

**Flammable Properties**

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames  
Flammable Liquid

**Flash Point**

40 °F / 4 °C

**Flammability Limits in Air**

**Upper**

2.8 %

**Lower**

0.39 %

**Suitable Extinguishing Media**

Dry Chemical.

#### Explosion Data

Sensitivity to Mechanical Impact  
Sensitivity to Static Discharge

None.  
Yes.

Specific hazards arising from the chemical

Containers may explode when heated or if contaminated with water. Flammable.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

#### HMIS

Health Hazard 1 \*

Flammability 3

Physical Hazard 1

Personal protection X

\* Chronic Health Hazard

### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Use personal protective equipment. Avoid breathing vapors or mists. Ventilate the area.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

Methods for Containment

Decontaminate floor with decontamination solution letting stand for at least 15 minutes. Soak up with inert absorbent material.

Methods for Cleaning Up

Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

Other information

DECONTAMINATION SOLUTION: Concentrated ammonia (3 - 8%), detergent (2%) and water (90 - 95%), a solution of Union Carbide's Tergitol TMN-10 (20%) and water (80%) or a solution of 50% isopropanol, 45% water, and 5% concentrated ammonia solution(% by weight).

### 7. HANDLING AND STORAGE

Advice on Safe Handling

Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use bonding and grounding when transferring materials. Use non-sparking tools and equipment.

Technical Measures/Storage Conditions

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat and sources of ignition. Protect the container from moisture. If moisture enters the container, do not reseal, pressure can build-up and cause container to burst.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL
METHYL AMYL KETONE	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m <sup>3</sup>
TITANIUM DIOXIDE	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust
CHROMIC OXIDE	TWA: 0.5 mg/m <sup>3</sup> Cr	TWA: 0.5 mg/m <sup>3</sup> Cr (vacated) TWA: 0.5 mg/m <sup>3</sup> Cr

ORGANIC TIN COMPOUND	STEL: 0.2 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> Sn S*	TWA: 0.1 mg/m <sup>3</sup> Sn (vacated) TWA: 0.1 mg/m <sup>3</sup> Sn (vacated) S*
----------------------	---	--

NIOSH IDLH: Immediately Dangerous to Life or Health

#### Engineering Measures

Air sampling should be done to measure airborne concentrations of the monomer of Hexamethylene Diisocyanate (HDI), the HDI polyisocyanate and organic solvents. Good industrial hygiene practice dictates that when isocyanate-containing coatings are spray applied, some form of respiratory protection should be worn. During the spray application of these coatings, the use of a supplied-air respirator (either positive pressure or continuous flow type) is mandatory when one or more of the following conditions exist: the airborne isocyanate concentrations are not known; or, the airborne isocyanate concentrations exceed ten times the exposure limits; or, no airborne solvent concentration exceeds its odor threshold; or, spraying is performed in a confined space. (See OSHA Confined Space Standard 29 CFR 1910.146.) A properly fitted air-purifying respirator (combination organic vapor and particulate), proven by test to be effective in isocyanate-containing spray paint environments, the airborne isocyanate concentrations are known to be below ten times the exposure limits; at least one solvent in the coating has a published odor threshold; and, at least one airborne solvent concentration is lower than its TLV but higher than its odor threshold. The odor of the solvent will then alert the respirator wearer to any breakdown of the respirator filters. FOR NON-SPRAY OPERATIONS: the same precautions, a local exhaust hood should be used to remove fumes during the welding or cutting operation, a fresh air supplied respirator should be worn during welding or cutting. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

#### Personal Protective Equipment

##### Eye/Face Protection

Tightly fitting safety goggles.

##### Skin and Body Protection

Solvent-resistant gloves. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse.

##### Respiratory Protection

Maintain adequate ventilation. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

##### Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State @20°C	Liquid	Appearance	Opaque
Odor	Solvent.	Flash Point	40 °F / 4 °C
Boiling Point	208 °F / 98 °C	Specific Gravity	1.09
Weight per Gallon (lbs/gal):	9.09		
Flammability Limits in Air			
Upper	2.8 %		
Lower	0.39 %		

### 10. STABILITY AND REACTIVITY

#### Stability

Stable under recommended storage conditions.

#### Incompatible Products

Water, epoxy catalysts, alcohols, glycol ethers, bases, metal complexes, and other active materials.



**Conditions to Avoid** None known based on information supplied.

**Hazardous Decomposition Products** Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**Hazardous Polymerization** Hazardous polymerization does not occur.

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

**Product Information** Long-term repeated exposure to Xylene may result in hearing loss.

### Component information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL AMYL KETONE	1670 mg/kg ( Rat )	12600 µL/kg ( Rabbit )	-
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE	-	-	18500 mg/m <sup>3</sup> ( Rat ) 1 h
TITANIUM DIOXIDE	10000 mg/kg ( Rat )	-	-
ORGANIC TIN COMPOUND	175 mg/kg ( Rat )	-	-

### Chronic Toxicity

**Product Information** Long-term repeated exposure to Xylene may result in hearing loss.

**Carcinogenicity** This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	IARC	ACGIH	NTP	OSHA
TITANIUM DIOXIDE	Group 2B	-	-	X
CHROMIC OXIDE	Group 3	-	-	-

### Legend:

**IARC: (International Agency for Research on Cancer)**  
Group 2B - Possibly Carcinogenic to Humans  
Group 3 - Not Classifiable as to Carcinogenicity in Humans  
**OSHA: (Occupational Safety & Health Administration)**  
X - Present

**Target Organ Effects** Central nervous system (CNS), Eyes, Lungs, Peripheral Nervous System (PNS), Respiratory system, Skin.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
METHYL AMYL KETONE	-	126-137: 96 h Pimephales promelas mg/L LC50 flow-through	-	-
ORGANIC TIN COMPOUND	-	2: 48 h Oryzias latipes mg/L LC50	-	-

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number** U239 D001

This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical Name	California Hazardous Waste Status
CHROMIC OXIDE	Toxic Corrosive Ignitable
ORGANIC TIN COMPOUND	Toxic

### 14. TRANSPORT INFORMATION

#### DOT

**Proper shipping name** Paint  
**Hazard class** 3  
**UN/ID No** UN1263  
**Packing Group** II  
**Description** UN1263, Paint, 3, II  
**Emergency Response Guide Number** 128

#### TDG

**Proper shipping name** Paint  
**Hazard class** 3  
**UN/ID No** UN1263  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

#### MEX

**Proper shipping name** Paint  
**Hazard class** 3  
**UN/ID No** UN1263  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

#### ICAO

**UN/ID No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

#### ICAO/IATA

**UN/ID No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**ERG Code** 3L  
**Description** UN1263, Paint, 3, II

**IMDG/IMO**

Proper shipping name Paint  
Hazard class 3  
UN/ID No UN1263  
Packing Group II  
EmS No. F-E, S-E  
Description UN1263, Paint, 3, II

**RID**

Proper shipping name Paint  
Hazard class 3  
UN/ID No UN1263  
Packing Group II  
Classification Code F1  
Description UN1263, Paint, 3, II

**ADR/RID**

Proper shipping name Paint  
Hazard class 3  
UN/ID No UN1263  
Packing Group II  
Classification Code F1  
Description UN1263, Paint, 3, II, (D/E)  
ADR/RID-Labels 3

**ADN**

Proper shipping name Paint  
Hazard class 3  
UN/ID No UN1263  
Packing Group II  
Classification Code F1  
Special Provisions 163, 640C, 650  
Description UN1263, Paint, 3, II  
Limited quantity 5 L  
Ventilation VE01

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
DSL/NDL Complies

**Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

**U.S. Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight	SARA 313 - Threshold Values %
CHROMIC OXIDE	1308-38-9	0% - 5%	1.0

**SARA 311/312 Hazard Categories**

Acute Health Hazard Yes

Chronic Health Hazard No  
Fire Hazard Yes  
Sudden Release of Pressure Hazard No  
Reactive Hazard No

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Chemical Name	CAS-No	Weight	HAPS data	VOC Chemicals	Class 1 Ozone Depleters	Class 2 Ozone Depleters
CHROMIC OXIDE	1308-38-9	1.1756	Present	-	-	-

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
CHROMIC OXIDE	-	X	-	-

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**U.S. State Regulations**

**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL AMYL KETONE	X	X	X	-	X
TITANIUM DIOXIDE	X	X	X	-	X
CHROMIC OXIDE	X	X	X	X	X
TERTIARY BUTYL ACETATE	X	X	X	-	X

**International Regulations**

**Mexico - Grade**

Serious risk, Grade 3

Chemical Name	Carcinogen Status	Exposure Limits
METHYL AMYL KETONE	-	Mexico: TWA 50 ppm Mexico: TWA 235 mg/m <sup>3</sup> Mexico: STEL 100 ppm Mexico: STEL 465 mg/m <sup>3</sup>
TITANIUM DIOXIDE	-	Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 20 mg/m <sup>3</sup>
CHROMIC OXIDE	-	Mexico: TWA 0.5 mg/m <sup>3</sup>
ORGANIC TIN COMPOUND	-	Mexico: TWA 0.1 mg/m <sup>3</sup> Mexico: STEL 0.2 mg/m <sup>3</sup>

**16. OTHER INFORMATION**



**DISCLAIMER**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

end