

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(See top of page)

2. COMPOSITION/INFORMATION ON INGREDIENTS

This product contains one or more reported carcinogens or suspected carcinogens which are noted below and in Section 11.

Component/Exposure Limits	CAS#	% by Wt.
METHYL ACETATE	79-20-9	25.91
ACGIH TLV/TWA - 200 PPM		
OSHA PEL - 200 PPM		
OTHER INFORMATION: 250 PPM = STEL		
BARIUM SULFATE	7727-43-7	20-30%
ACGIH TLV/TWA - 10 MG/M3		
OSHA PEL - 10 MG/M3 (NUISANCE DUST)		
OTHER INFORMATION: The EPA delisted Barium Sulfate from the June 28th, 1994 Federal Register. (59FR33205)		
EPOXY RESIN	25036-25-3	10-20%
ACGIH TLV/TWA - 10 MG/M3 (Dust) 5 MG/M3 (Respirable)		
OSHA PEL - 15 MG/M3 (Dust) 5 MG/M3 (Respirable)		
BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL)	098-56-6	9.15
ACGIH TLV/TWA - Not Established		
OSHA PEL - CEL : 25 PPM 8 HR TWA		
METHYL AMYL KETONE	110-43-0	5.03
ACGIH TLV/TWA - 50 PPM		
OSHA PEL - 100 PPM		
TITANIUM DIOXIDE	13463-67-7	0-10%
ACGIH TLV/TWA - 10 MG/M3		
OSHA PEL - 10 MG/M3		
BUTYL ACETATE	123-86-4	1.46
ACGIH TLV/TWA - 150 PPM		
OSHA PEL - 150 PPM		
OTHER LIMITS: 200 PPM = STEL		
YELLOW IRON OXIDE PIGMENT	51274-00-1	0-10%
ACGIH TLV/TWA - 5 MG/M3		
OSHA PEL - 10 PPM		
OTHER INFORMATION:		
Exposure limits are for Iron Oxide fume.		
CARBON BLACK	1333-86-4	.69
ACGIH TLV/TWA - 3.5 MG/M3		
OSHA PEL - 3.5 MG/M3		
OTHER INFORMATION: Listed by IARC as Group 2B, possibly carcinogenic to humans. See Section 11.		

Date Printed: 3/6/2006

Page: 2

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if inhaled. May cause the following effects:

Nose, throat and respiratory tract irritation. Allergic respiratory reaction.

May cause lung damage. Eye and skin irritation. Allergic skin reaction.

FLAMMABLE LIQUID

Keep away from heat, sparks, and flame.

Vapors may cause flash fire.

Toxic gases/fumes are given off during burning or thermal decomposition.

EYE CONTACT:

Severe irritant. Prolonged contact may result in chemical burns to the eyes. Blindness may occur.

SKIN CONTACT:

Severe irritant. Contact with skin causes severe irritation and pain. Prolonged contact may result in chemical burns.

Product may be absorbed through the skin in harmful amounts.

PRIMARY ROUTES OF ENTRY:

Skin absorption.

Dermal and inhalation.

INGESTION:

If swallowed, consult a physician immediately.

May cause mucosal damage.

INHALATION:

Anesthetic. Can cause irritation of the respiratory tract or acute nervous system depression characterized by the following progressive steps if severe overexposure is continued: headache, dizziness, staggering gait, confusion or unconsciousness.

CHRONIC INFORMATION:

See Section 11.

CARCINOGENICITY:

See Section 11.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Date Printed: 3/6/2006

Page: 3

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

Asthma and other respiratory ailments; chemical sensitization.

4. FIRST AID MEASURES

EYE CONTACT:

Flush immediately with large amounts of running water for at least 15 minutes while lifting eyelids. Take to a physician for medical treatment.

SKIN CONTACT:

Wash affected areas with soap and water. Remove contaminated clothing and wash before reuse. Consult a physician if irritation develops or persists.

INGESTION:

If swallowed, CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

NOTE TO PHYSICIANS: Symptoms may not appear for several hours. Keep under medical supervision for at least 48 hours.

INHALATION:

Remove from exposure. Restore breathing. Keep warm and quiet. Notify a physician.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION PROPERTIES:

FLASH POINT (deg.F):

9

METHOD:

Tag Closed Cup

FLAMMABLE LIMITS % :

Lower limit: 0.9

Upper limit: 16

AUTOIGNITION TEMPERATURE:

N/A

EXTINGUISHING MEDIA:

Carbon Dioxide, Dry Chemical or Foam.

FIREFIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat,

Date Printed: 3/6/2006

Page: 4

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

electrical equipment, sparks and open flames.
Closed container may explode when exposed to extreme heat.
Do not apply to hot surfaces. Never use welding or cutting
torch on or near product container (even empty) because
product (even residue) can ignite explosively.
Full protective equipment including self-contained breathing
apparatus should be worn.
Water spray may be ineffective. Water may be used to cool
closed containers to prevent pressure build-up or possible
autoignition or explosion when exposed to extreme heat. If
water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED :

Evacuate all non-essential personnel and remove all sources
of ignition (flames, hot surfaces, electrical, static and
frictional sparks). Ventilate area. Equip clean-up crew with
appropriate protective equipment. Avoid breathing vapors.
Avoid skin contact. Prevent entry into drains, sewers and
waterways. Notify appropriate authorities if necessary.
Contain and remove with inert absorbent and nonsparking
tools.

7. HANDLING AND STORAGE

HANDLING:

Use only with adequate ventilation. Avoid prolonged
breathing of vapors. Wear an appropriate, properly fitted
respirator (NIOSH/MSHA approved) during and after
application unless air monitoring demonstrates that vapor/
mist levels are below applicable exposure limits. Follow
respirator manufacturer's directions for use.
Use grounding and bonding connection when transferring
material to prevent static discharge, fire or explosion.
Avoid free fall of liquid in excess of a few inches. Use
sparkproof tools and explosion proof equipment.

STORAGE:

Do not store above 120 F or below 32 F. Store large
quantities in buildings designed to comply with OSHA's 29
CFR 1910.106. Keep away from heat, sparks and open flame.
Keep containers closed when not in use. Keep closures tight
and upright to prevent leakage.
Emptied containers may retain hazardous residue. Follow all
hazard precautions in this data sheet until container is

Date Printed: 3/6/2006

Page: 5

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

thoroughly cleaned or destroyed. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below current applicable OSHA safety and health requirements in the mixing, application and curing areas; and to remove decomposition products during welding and flame cutting on surfaces coated with this product.

RESPIRATORY PROTECTION:

When spray applied and when used in limited ventilation areas, wear a NIOSH/MSHA approved organic vapor/particulate respirator designed to remove a combination of particulate, gas and vapor. When used in confined areas or poorly ventilated areas, use a NIOSH/MSHA approved air line type respirator or hood. During sanding or grinding operations, use a NIOSH approved particulate respirator to remove solid airborne particles of sanding dust. Use NIOSH approved respirators when flame cutting, welding or hazing material coated with this product. Observe OSHA regulations for respirator use (29 CFR 1910.134). Air monitoring of the workplace may be required to determine appropriate respirator selection.

EYE PROTECTION:

Use safety eyewear with splash guards or side shields. A full face shield may be appropriate. Contact lenses should not be worn.

SKIN PROTECTION:

It is good industrial hygiene practice to minimize skin contact. Chemical resistant gloves are required for prolonged or repeated contact. An apron may be appropriate to protect against skin contact. Prevent prolonged skin contact with contaminated clothing. Wash contaminated clothing before reuse.

OTHER PROTECTIVE EQUIPMENT AND GUIDELINES:

Safety showers and eye wash stations should be available.

Date Printed: 3/6/2006

Page: 6

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

Educate and train employees in the safe use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:

Liquid.

APPEARANCE:

Opaque.

ODOR:

Solvent odor.

VOC (LB/GL):

1.33 lb/gl

VOC (grams/liter):

159 g/l

WEIGHT PER GALLON:

10.9218 lb/gl

SPECIFIC GRAVITY:

1.3117

%EXEMPT SOLVENT by WEIGHT:

35.06

%EXEMPT SOLVENT by VOLUME:

45.302

BOILING POINT (deg. F):

55.8

WATER SOLUBILITY:

Negligible.

FREEZING POINT (deg. F):

N/A

10. STABILITY AND REACTIVITY

STABILITY:

Stable.

HAZARDOUS POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce hazardous fumes when heated to decomposition as in welding. Fumes may contain the following:
Carbon Monoxide, Carbon Dioxide and other toxic vapors depending upon the temperature reached.

INCOMPATIBILITIES (MATERIALS TO AVOID):

Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

Date Printed: 3/6/2006

Page: 7

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

ACUTE EFFECTS:

Carbon Black

Oral Rat LD50 = >8 g/kg

Titanium Dioxide:

Oral ALD Rat = >24,000 mg/kg

Dermal ALD Rabbit = >10,000 mg/m3

Inhalation 4-hour ALC Rat = >6.82 mg/l

Has not been tested as a whole for acute effects.

CHRONIC EFFECTS:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage, liver and kidney damage. Long term overexposure effects are not currently known.

Has not been tested as a whole for chronic effects.

CARCINOGENICITY:

Contains carbon black which has been listed by IARC as a possible human carcinogen (group 2B) based upon laboratory animal inhalation studies.

Has not been tested as a whole for carcinogenicity effects.

MUTAGENICITY:

Has not been tested as a whole for mutagenicity effects.

REPRODUCTIVE EFFECTS:

Has not been tested as a whole for reproductive effects.

DEVELOPMENTAL EFFECTS:

Has not been tested as a whole for developmental effects.

12. ECOLOGICAL INFORMATION

ECOLOGICAL EFFECTS:

Has not been tested as a whole for ecological effects.

13. DISPOSAL CONSIDERATIONS

Date Printed: 3/6/2006

Page: 8

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

DISPOSAL METHODS:

Recycle, fuel blend or incinerate.
Dispose of in accordance with applicable laws and regulations. It is the responsibility of the owner of the waste to dispose of it properly. Laboratory analysis is recommended to profile the waste for proper disposal determination.

U.S E.P.A WASTE NUMBER AND DESCRIPTION:

D001 Waste Paint

HAZARDOUS WASTE CHARACTERISTICS:

Ignitable.

14. TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME:

Paint

UN NUMBER:

UN1263

DOT HAZARD CLASS:

3

DOT LABEL:

Flammable Liquid

DOT PACKAGING GROUP:

PG II

U.S POSTAL SERVICE:

Will not handle.

15. REGULATORY INFORMATION

(Not meant to be all inclusive - selected regulations represented)

TSCA STATUS:

All ingredients are listed on the TSCA inventory.

STATE REGULATIONS:

This product may contain chemicals that fall under individual state Right-to-Know regulatory requirements. See Section 2 for material

Date Printed: 3/6/2006

Page: 9

Product Code: 16959AEF-LVOC

Product Name: 16081 GRAY EPOXZEN, MIL-PRF-22750F PART A

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

24-hour Emergency Phone: Chemtrec: 800-424-9300

listings. For details on regulatory requirements, contact the appropriate agency in your state.

16. OTHER INFORMATION

Date of issue: 3/6/2006

Last Revision Date: 02/27/06

HMIS Information

HEALTH: 2

FLAMMABILITY: 4

REACTIVITY: 1

PERSONAL PROTECTIVE EQUIPMENT:

DISCLAIMER:

This MSDS is provided as an informational resource only. The information is received from a combination of sources, including raw material suppliers and is believed to be reliable and accurate. It does not intend to be all-inclusive and shall only be used as a guide. Changing reporting requirements and other uncontrolled variables make it impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to verify its information as well as determine the proper personal protection based on conditions of use. The buyer assumes all responsibility for the use and handling of this product in accordance with the Federal, State and Local laws and regulations. Hentzen Coatings, Inc. makes no representation or warranty regarding the accuracy of this information nor that the information or data will not change.